

ZL130ZH

SPECIFICATION



ENGINE	
ENGINE TYPE	SINGLE CYLINDER, AIR COOLING, 4-STROKE
DISPLACEMENT	122.8ML
COMPRESSION RATIO	9.5:1
MAX POWER OUTPUT	6.1 / 7500 KW/R/MIN
MAX TORQUE	9.0 / 5500 N-M/R/MIN
CLUTCH	
WET MULTI-PLATE, PRESSURE SPLASH	
TRANSMISSION & REVERSE	
4 FORWARD GEARS + 1 REVERSE	
STEERING MECHANISM	
STEERING HANDLE BAR	
CHASSIS	
40×60 RECTANGULAR STEEL TUBE	
FRONT SUSPENSION	
130 HYDRAULIC SHOCK ABSORBER	
REAR SUSPENSION	
INTEGRATED 6 PCS LEAF SPRING, TAPER DIFFERENTIAL BOX REAR AXLE	
BRAKING SYSTEM	
FR 130 / RR 160, MECHANICAL BRAKING	
WHEEL TIRE	
FR 3.75-12, RR 4.00-12	
BATTERY	
12V / 9AH	
STARTING METHOD	
ELECTRIC / KICK STARTER	
FUEL TANK	
GASOLINE, 7L	
FUEL CONSUMPTION	
≤288	
GROUND CLEARANCE	
160MM	
MAX SPEED	
50KM/H	
OVERALL DIMENSION	
WHEEL BASE	1950MM
DIMENSION	2900×900×1330MM
CARGO BOX SIZE	1400×900MM
VEHICLE WEIGHT	
KERB 260KGS, PAY 260KGS	
Q'TY LOADED IN CONTAINER	
25 SETS IN CKD / 20GP; 49 SETS IN CKD / 40HQ	

