

ZL150ZH-Q



SPECIFICATION

ENGINE	
ENGINE TYPE	SINGLE CYLINDER, AIR COOLING, 4-STROKE
DISPLACEMENT	149ML
COMPRESSION RATIO	9.1:1
MAX POWER OUTPUT	8.5 / 8000 KW/R/MIN
MAX TORQUE	10 / 7500 N-M/R/MIN
CLUTCH	
WET MULTI-PLATE,PRESSURE SPLASH	
TRANSMISSION & REVERSE	
5 FORWARD GEARS + 1 REVERSE	
STEERING MECHANISM	
STEERING HANDLE BAR	
CHASSIS	
40×80 RECTANGULAR TUBE, BALL TIPPED BUMPER, CHANGPAO BIG FOOTREST	
FRONT SUSPENSION	
232# WITH OUTER SPRING Φ43 CHOPPER SHOCK ABSORBER	
REAR SUSPENSION	
INTEGRATED 5 PCS LEAF SPRING; LIGHT DUTY GII REAR AXLE WITH BOOSTER	
BRAKING SYSTEM	
FR 130, RR 180, MECHANICAL BRAKING	
WHEEL TIRE	
FR / RR 4.50-12	
BATTERY	
12V / 9AH	
STARTING METHOD	
ELECTRIC /KICK STARTER	
FUEL TANK	
GASOLINE, 12L	
FUEL CONSUMPTION	
≤354	
GROUND CLEARANCE	
160MM	
MAX SPEED	
55KM/H	
OVERALL DIMENSION	
WHEEL BASE	2200MM
DIMENSION	3290×1200×1380MM
CARGO BOX SIZE	1800×1200MM
VEHICLE WEIGHT	
KERB 320KGS, PAY 300KGS	
Q'TY LOADED IN CONTAINER	
30 SETS IN CKD / 20GP; 60 SETS IN CKD / 40HQ	
OPTIONAL PARTS	
SEMI-CABIN	

