

ZL150ZH-TZ



SPECIFICATION

ENGINE	
ENGINE TYPE	SINGLE CYLINDER, AIR COOLING, 4-STROKE
DISPLACEMENT	149ML
COMPRESSION RATIO	9.1:1
MAX POWER OUTPUT	8.5 / 8000 KW/R/MIN
MAX TORQUE	10 / 7500 N·M/R/MIN
CLUTCH	
WET MULTI-PLATE, PRESSURE SPLASH	
TRANSMISSION & REVERSE	
5 FORWARD GEARS + 1 REVERSE	
STEERING MECHANISM	
STEERING HANDLE BAR	
CHASSIS	
FR 40×80 RR 40×60 RECTANGULAR STEEL TUBE	
FRONT SUSPENSION	
SPECIAL FRONT SHOCK ABSORBER	
REAR SUSPENSION	
COMBINED 3+2 PCS LEAF SPRING, CHAN'AN REAR AXLE (5 BOLTS) WITH DAMPER	
BRAKING SYSTEM	
FR 160, RR 220, MECHANICAL BRAKING	
WHEEL TIRE	
FR / RR 5.00-12	
BATTERY	
12V / 9AH	
STARTING METHOD	
ELECTRIC / KICK STARTER	
FUEL TANK	
GASOLINE, 12L	
FUEL CONSUMPTION	
≤354	
GROUND CLEARANCE	
160MM	
MAX SPEED	
55KM/H	
OVERALL DIMENSION	
WHEEL BASE	2370MM
DIMENSION	3300×1350×1380MM
CARGO BOX SIZE	1800×1200MM
VEHICLE WEIGHT	
KERB 360KGS, PAY 300KGS	
Q'TY LOADED IN CONTAINER	
22 SETS IN CKD / 20GP ; 45 SETS IN CKD / 40HQ	
OPTIONAL PARTS	
1. SEMI-CABIN 2. DUMPER SYSTEM	





Strong Fr Shock Absorber



Comfortable seat



Light Duty Rear Axle



Quality Tyre



Sleek Fuel Tank



Storage Box



Meter



Headlamp



Keel Chassis