

ZL200ZH-5N



SPECIFICATION

ENGINE	
ENGINE TYPE	SINGLE CYLINDER, WATER COOLING, 4-STROKE
DISPLACEMENT	197ML
COMPRESSION RATIO	10.2:1
MAX POWER OUTPUT	10.3 / 7500 KW/R/MIN
MAX TORQUE	14.2 / 6000 N·M/R/MIN
CLUTCH	WET MULTI-PLATE, PRESSURE SPLASH
TRANSMISSION & REVERSE	5 FORWARD GEARS + 1 REVERSE
STEERING MECHANISM	STEERING HANDLE BAR
CHASSIS	FR/RR 50×100 RECTANGULAR STEEL TUBE
FRONT SUSPENSION	ZONLON OFF-ROAD SHOCK ABSORBER
REAR SUSPENSION	7 PCS PICKUP LEAF SPRING, RIBBED JLW SEMI-FLOAT REAR AXLE WITH BOOSTER
BRAKING SYSTEM	FR 130, RR 220, MECHANICAL BRAKING
WHEEL TIRE	FR / RR 4.50-12
BATTERY	12V / 28AH
STARTING METHOD	ELECTRIC / KICK STARTER
FUEL TANK	GASOLINE, 12L
FUEL CONSUMPTION	≤354
GROUND CLEARANCE	160MM
MAX SPEED	60KM/H
OVERALL DIMENSION	
WHEEL BASE	2200MM
DIMENSION	3400×1350×1550MM
CARGO BOX SIZE	1800×1350MM
VEHICLE WEIGHT	KERB 450KGS, PAY 350KGS
Q'TY LOADED IN CONTAINER	24 SETS IN CKD / 20GP; 52 SETS IN CKD / 40HQ
OPTIONAL PARTS	1. SEMI-CABIN 2. CARGO BOX SIZE AND TYPE OPTIONAL ON REQUEST 3. HYDRAULIC BRAKING SYSTEM 4. DUMPER SYSTEM

