

BAJA TIPPER ZL200ZH-BT



SPECIFICATION

ENGINE	
ENGINE TYPE	SINGLE CYLINDER, WATER COOLING, 4-STROKE
DISPLACEMENT	197ML
COMPRESSION RATIO	10.2:1
MAX POWER OUTPUT	10.3 / 7500 KW/R/MIN
MAX TORQUE	14.2 / 6000 N-M/R/MIN
CLUTCH	
WET, MULTI-PLATE, PRESSURE SPLASH	
TRANSMISSION & REVERSE	
5 FORWARD GEARS + 1 REVERSE	
TIPPER SYSTEM	
SINGLE, 2-STAGE, OIL HYDRAULIC CYLINDER	
STEERING MECHANISM	
STEERING HANDLE BAR	
CHASSIS	
FR 40×100, RR 50×100 RECTANGULAR STEEL TUBE	
FRONT SUSPENSION	
TYPE 800 W270 SOLO FRONT SHOCK ABSORBER WITH INTERCHANGEABLE WHEEL	
REAR SUSPENSION	
INTEGRATED PICKUP 7 PCS LEAF SPRING, CHAN'AN REAR AXLE	
BRAKING SYSTEM	
FR 130, RR 220, MECHANICAL BRAKING	
WHEEL TIRE	
FR / RR 4.50-12	
BATTERY	
12V / 9AH	
STARTING METHOD	
ELECTRIC / KICK STARTER	
FUEL TANK	
GASOLINE, 12L	
FUEL CONSUMPTION	
≤354	
GROUND CLEARANCE	
160MM	
MAX SPEED	
60KM/H	
OVERALL DIMENSION	
WHEEL BASE	2350MM
DIMENSION	3500×1350×1820MM
CARGO BOX SIZE	2000×1350×590MM
VEHICLE WEIGHT	
KERB 500KGS, PAY 350KGS	
Q'TY LOADED IN CONTAINER	
10 SETS IN CKD / 20GP; 22 SETS IN CKD / 40HQ	

