

# ZL200ZK-7S



# ZL200ZK-5S



## SPECIFICATION

ENGINE	
ENGINE TYPE	SINGLE CYLINDER, WATER COOLING, 4-STROKE
DISPLACEMENT	197ML
COMPRESSION RATIO	10.2:1
MAX POWER OUTPUT	10.3 / 7500 KW/R/MIN
MAX TORQUE	14.2 / 6000 N·M/R/MIN
CLUTCH	
WET, MULTI-PLATE, PRESSURE SPLASH	
TRANSMISSION & REVERSE	
5 FORWARD GEARS + 1 REVERSE	
STEERING MECHANISM	
STEERING HANDLE BAR	
CHASSIS	
FRONT 40×100, REAR 50×100 RECTANGULAR STEEL TUBE	
FRONT SUSPENSION	
ELEVATED FRONT SHOCK ABSORBER	
REAR SUSPENSION	
INTEGRATED OUTER MOUNTING 7 PCS LEAF SPRING, CHAN'AN REAR AXLE	
BRAKING SYSTEM	
FR 130, RR 180, MECHANICAL BRAKING	
WHEEL TIRE	
FR / RR 4.50-12	
BATTERY	
12V / 9AH	
STARTING METHOD	
ELECTRIC / KICK STARTER	
FUEL TANK	
GASOLINE, 12L	
FUEL CONSUMPTION	
≤354	
GROUND CLEARANCE	
160MM	
MAX SPEED	
55KM/H	
OVERALL DIMENSION	
WHEEL BASE	2470MM / 2270MM
DIMENSION	3300×1250×1200MM / 3100×1250×1200MM
SEATS CAPACITY	7 / 5 PASSENGERS
VEHICLE WEIGHT	
KERB 370 / 350KGS, PAY 750 / 600KGS	
Q'TY LOADED IN CONTAINER	
12 SETS IN CKD / 20GP; 28 SETS IN CKD / 40HQ	

